



Commercial Series J22CE820 22" LED HDTV



Volume Bo



Bed 1/2/3 US Compatible Prog



USB Clone Programming



Commercial Interface



Eco Friendly




2 Year Replacement

Commercial Features

DirecTV DRE IR pass-through	. Allows the TV to pass commands from the TV remote to the DirecTV box.
ATSC Tuning Mode	. Select between physical or virtual channel numbers, giving your headend distribution system optimal flexibility.
Antenna/Cable Merge	. Ability to merge different video frequencies into a single channel lineup.
AUX Inputs In Channel List	. Adds inputs to the channel list to allow access using the CH buttons.
Auto Detect Side A/V	. Allows users to easily connect peripheral devices to side input without use of remote.
Direct Tuning Access	. Prevents guests from accessing channels that are not programmed in the TV channel list.
Channel Labeling	. Allows channels to have individual customized labels and numbers.
Initial Channel	. Sets the input/channel for the TV to tune when turned on.
Channel Hold	. Locks current channel to prevent channel changes by user.
Initial CC	. Choose a close caption mode when TV is turned on.
Volume Limiter/Initial Volume	. Sets the minimum, maximum and initial volume settings when the TV is turned on.
USB Cloning Capable	. Allows rapid duplication of TV configurations for easy installation and maintenance.

USB File Play	. Allows guests to play MP3 and JPG files, as well as charge mobile devices.
Auto Power On	. Selectable power state of the TV after a power cycle.
Auto Power Off	. Allows the TV to turn off after a selectable period of inactivity.
Master & Guest Remotes	. Separate remotes for configuration and operation.
Bed 1/2/3 Capable	. Allows simultaneous control of multiple TVs in the same room.
Front Panel/Menu Lockout	. Allows facility to disable front panel and menu controls to make television "tamper proof".
Splash Screen	. Ability to add facility logo to startup screen using a JPG file and USB.
Control Port	. RS-232C allows for integration with "infotainment" providers and video conferencing equipment.
Energy Saving Features	. No signal/activity power off, ambient back lighting control, less than .5 watt in standby mode, low power LED.
Matte Black Finish	An alamant land, that madeta statistic forms
	prints.

Specifications



Cabinet Description	
Cabinet Style	Wall Mount
Cabinet Color	Matte Black
VESA Standard	100mm×100mm/M4
Set (w/o Stand) W×H×D	21.06"×14.13"×1.87"
Set (w/o Stand) Weight	7.94lbs
Carton W×H×D	23.43"×17.13"×4.45"
Shipping Weight	11.24lbs


Inputs/Outputs	
HDMI In	2
PC Video In (VGA D-sub 15)	1
PC Audio In	1
Component In (Y,Pb,Pr+Audio L/R)	1 (Mini Jack 3.5mm×2)
Composite In (Video+Audio L/R)	2 (Mini Jack 3.5mm, RCA)
S-Video In	1
Audio Out	1 (Mini Jack 3.5mm)
RF In (Antenna/Cable)	1
Service Port (RS-232)	1 (Mini Jack 2.5mm)
USB In	


Power	
Rating	AC 115V 60Hz
Power Consumption	30W
Power Consumption (Standby)	<1W

Power Cord	Yes (Hospital Grade
Composite Breakout Cable	Ye
Component Breakout Cable	Ye
Manual	Installation/Operating
Installer Remote Control (KM38R01)	Not Included (Optiona
Guest Remote Control (KM38R02)	Not Included (Optiona
Wall Mount	Not Included (Optiona


Certifications	
FCC	Yes
UL, cUL Listed	Yes
RoHS Compliant	Yes
CEC Compliant	Yes

Service/Limited Warranty	
Limited Warranty	2 Years (Replacement























RCA and associated trademarks of Technicolor SA used under license to DTI Services, LLC.

